Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	1. Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. 2. Check that all bolts and screws are tight and retighten if necessary. 3. Recommendation: apply wood preservative wax (www.complex-farben.eu) once a year. Sphere suspension 4. Clean with stainless steel spray (www.kim-tec.de) using a clean cloth. 5. Check that the spheres form an exact line, readjust if necessary (see detailed diagram*). 6. Replace spheres if necessary. Structural stability	
Impulse Spheres Order No. 10.11000 angled rail detailed diagram stop nut M6 bottom	7. In order to check that the equipment is securely fastened to the ground, uncover the foundations once a year. stop nut M6 top approx. 1 mm gap eyebolt M6x50 * Note on step 5: The nuts at the bottom of the angled rails must not be tightened to the end of their threads (approx. 1 mm gap, see detailed diagram).	Special notes, e.g. for repairs
7	Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action All work carried out, everything is in order	
For spare parts refer to back of page.	Maintenance carried out by: to back of page.	


Spare Parts Impulse Spheres Order No. 10.11000



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

Order No. Spare part

Order No. Spare part



10.99904 sphere suspension gear with 9 spheres



10.99934 set of ropes with eyebolts and nuts w/o illustr. (for 9 spheres)