Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance	
Playground	Wooden parts		
Date of installation	Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks.		
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static	Check all bolts and screws are tight and retighten if necessary.		
equipment equipment at least once a year.	Function		
Intervals for maintenance work and checks generally depend on	Check pretension. Load the rope knot with 75 kg, may sink max. 50 mm, if necessary retighten the entire		
the locationthe usagethe frequency of use	pyramid evenly.		
- possible vandalism	Joints		
For more details see also "General instructions for maintenance of	 Grease ball bearings via the lubricating nipples (see detailed diagram C). 		
playgrounds". Small Net Pyramid	Check all bolts and screws are tight and retighten if necessary.		
Order No. 13.01000/13.01100	Ropes		
Middle Net Pyramid Order No. 13.02000/13.02100	Check for wear and tear. Replace if steel reinforcement is damaged.		
Big Net Pyramid	7. Check S-clamps and swages		
Order No. 13.03000/13.03100	Structural stability		
	Uncover the foundation once a year in order to check all parts of steel for corrosion.		
			repairs
			e.g. for
<u> </u>			notes,
			Special notes, e.g. for repairs
(3)	Repair not carried out, it is still possible to play on equipment		
detailed diagram C	Repair not carried out, equipment is taken out of action		
	All work carried out, everything is in order		
4	Maintenance carried out by:	-	
	Date		