430

Order No. 3.19032 **High Swing special** for attachment to corner on

285 260

© Richter Spielgeräte GmbH

Square Tower with roof 2.00 m (Order No. L3.20600)

430





175



For a description of the materials used for the attachment swings, please refer to Movement > Swinging.

Dimensions

(small deviations possible)

Order No. 3.19032	
Height	3 00 m
Vertical clearance	2.80 m
Length	2.60 m
Width	2.25 m
Weight	130 kg
-	5

Order No. 3.19042 **High Twin Swing special**

Height	3.00 m
Vertical clearance	2.80 m
Length	3.80 m
Width	2.25 m
Weight	150 kg

Components

Order No. 3.19032

- 2 Stand posts with steel feet
- 1 Cross beam made of steel with joints
- 1 Swing seat with chains

Order No. 3.19042

- 2 Stand posts with steel feet
- 1 Cross beam made of steel with joints
- 2 Swing seats with chains

Installation information

Surfacing requirements corresponding to a fall height of \leq 2.00 m (please refer to price list for more detailed information)

Foundations 2 items 60 x 70 x 40 cm Excavation depth 60 cm

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions. Technical changes reserved.



3.19032



info@ludocrea.ch

|

Order No. 3.19042 **High Twin Swing special** for attachment to corner on Square Tower with roof 2.00 m (Order No. L3.20600)



225 860

Safety check according to DIN EN 1176



Scale 1:100

Order No. L3.69103 ≤ 2.00 m Order No. L3.69105 / L3.69350 ≤ 1.50 m (please refer to price list for more detailed information)

Foundations

Order No. L3.69103 / L3.69105 2 items 50 x 50 x 40 cm Excavation depth 80 cm 2 items 70 x 55 x 60 cm Excavation depth 80 cm Order No. L3.69350 1 item 60 x 60 x 60 cm Excavation depth 80 cm 1 item 55 x 40 x 30 cm Excavation depth 50 cm



L3.69350

Technical information

Wooden parts made of non-impregnated mountain larch

Richter Hercules type rope

Richter Hercules type rope, a combination of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm, laid and glued with very good abrasion resistance, strong sheathing even in the case of damage by puncturing

Aluminium rope pressing

Rope connection fixed

Aluminium rope pressing, cylindrically pressed, with rounded ends

S-connectors

S-connectors Ø 8.1 mm. made of high-quality stainless steel, rounded

Fixed rope connection without dangerous openings. Screw connection





Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



Order No. L3.69103 / L3.69105

Inclined Climbing Net As above, but in addition with

Core-free

Sawn-timbers core-free, thus decreasing occurrences of cracking and undesired changes in shape



Order No. L3.69350 **Vertical Climbing Net**

As above, but in addition with

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced

For more detailed explanation of the quality characteristics see price list.

Firemen's pole made of stainless steel, Ø 42 mm

Dimensions

(small deviations possible)

Order No. L3.69103 Inclined Climbing Net	
Net	1.00 x 2.65 m
Order No. L3.69105	
Inclined Climbing Net	
Net	1.00 x 2.20 m
Weight	180 / 155 kg
Order No. L3.69350	-
Vertical Climbing Net	
Height of net	2.00 m
Net size	1.75 x 2.50 m
Width	3.20 m
Weight	70 kg

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions. Technical changes reserved.



and tensioning levers

Order No. L3.69350

with steel foot 1 Bent fireman's pole

2 Stand posts with steel feet

1 Vertical net with 1 stand post

L3.69105