Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below: Proof of maintenance	
Playground	 Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. Check all bolts and screws are tight and retighten if necessary. Swing suspension Make sure that the joints move smoothly. Make sure that the swivels move smoothly, apply grease if required. Check welds of metal cross beam for cracks. Check chain and connections to chain, the first chain link must be locked; Check wear on contact surfaces between first and second chain link. Swing seat Replace swing seat if metal parts are exposed. Check the swing seat for a minimum ground clearance of at least 40 cm. Structural stability In order to check the steel feet for corrosion, uncover the foundation once a year. 	Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action All work carried out, everything is in order	
For spare parts refer to back of page.	Maintenance carried out by: Date	

Spare Parts Single Swing special Order No. 3.19802



Please note that the safety standards of the equipment must not be affected. Therefore, **only original parts** should be used for repair.

	Ш	
Order No.	Spare part	
0.93000	Rubber Swing Seat	
0.93010	Rubber Swing Seat with 4 eyelet bolts	
0.93020	Rubber Swing Seat with 4 short V-chains	
0.93090	U-shackle with swivel	
0.88150	Brass Bush for Swing Joint	
0.20010	Stainless Steel Machine Bolt, M8x55 with locking nut	
0.20020	Stainless Steel Machine Bolt, M8x28 with locking nut	
	Hammo O	