En-EN 14.02.2023

COPYRIGHT © RICHTER SPIELGERÄTE GMBH

Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground Date of installation Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year. Intervals for maintenance work and checks generally depend on - location - usage - frequency of use - possible vandalism For more details see also our general instructions for maintenance of playgrounds! Stainless Steel Slide width 0.45 m, with 1 wave Order No. 3.63220 height 3.00 m Order No. 3.63230 height 3.50 m	<ul> <li>Slide <ol> <li>Check for vandalism.</li> <li>Check bolts and screws on the base equipment are tight and retighten if necessary.</li> </ol> </li> <li>Structural stability <ol> <li>In order to check the stability of the foundations or the steel feet for corrosion, uncover the foundation once a year.</li> </ol> </li> <li>Note For slides installed on a slope check that the ground shape has not changed in such a way that foundations are exposed.</li></ul>	Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action All work carried out,	
For spare parts refer to back of page.	Maintenance carried out by:	

## Page 2

