This copy may be copied for maintenance of Richter play equipment.		Page 1
Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Wooden parts	
Date of installation Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	 Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. 	
	2. Check that all bolts and screws are tight and retighten if necessary.	
Intervals for maintenance work and checks generally depend on	 Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm. 	
 location usage frequency of use possible vandalism 	4. Recommendation : apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.	
For more details see also our general instructions for maintenance of playgrounds!	Structural stability	
	5. In order to check steel feet for corrosion, uncover the foundations once a year.	
<section-header></section-header>		Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
	Maintenance carried out by:	
	Date	

COPYRIGHT © RICHTER SPIELGERÄTE GMBH