## Instructions for wear The equipment must be checked for correct Proof of operation and safety, especially the points maintenance checks of play equipment listed below: Structural stability Playground..... 1. Uncover the foundations once a year in order Date of installation ..... to check the structural stability as follows: - wood for rot Checks depend on the type of equipment. - steel for corrosion Any equipment with moving parts must - anchoring to the ground for stability be checked at least twice a year, static - condition of concrete foundations equipment at least once a year. Check that all bolts and screws as well as all Intervals for maintenance work and checks generally depend on wood joints are tight, retighten if necessary. - the location Wooden parts - the usage - the frequency of use 3. Check for rot and, if necessary, smooth out - possible vandalism splinters and round off sharp edges and cracks. For more details see also "General instructions for maintenance of Check steps for wear and tear: at least 2/3 playgrounds". of the material should be left, replace if necessary. **Totter Trail Type 02** Recommendation: apply paraffin wax to the end grain areas once a year, especially Order No. 4.03020 info@ludocrea.ch near the ground; please refer to Order No. 0.90100, 1 litre. Ropes and rope connections 6. Check that ropes are securely connected, retighten if necessary. 7. Check ropes for wear and tear, if the steel reinforcement is damaged it is imperative 675 03 they be replaced. Special notes, e.g. for repairs 4 +4] Giswil Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action .udoCrea.ch GmbH All work carried out, everything is in order Maintenance carried out by: ..... Date ......