Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Function  1. Make sure the pump mechanism moves smoothly.  2. Check water hoses for wear and tear; replace if necessary. To do this, loosen lid bolts (Allen key No. 4) and remove upper part including pump mechanism.  3. Clean sieve of pressure reduction valve if soiled.  Valve and cartridge  4. When replacing the entire valve or the cartridge, pump several times until the automatic shutoff engages (if necessary, shut off the water several times and then turn on again).  Structural stability  5. Check anchoring to the ground every 12 months, retighten screws and bolts if necessary.  Note  Prior to the start of the frost period, turn off water supply and remove the mushroom pump. It is necessary to remove at least the upper part. If the housing part is to remain on site, close it with the winter lid.  If a programmable rinsing device (No. 5.18022) is fitted, the time switch is particularly vulnerable to frost damage as it cannot be drained. Therefore, it is imperative the pump be dismantled. Store the pump protected from frost.	Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
	Maintenance carried out by:	
	Date	

	c	
	C	)
	C	)
	Ø	)
	Ć	)
	into(a)   Into or a	)
	2	
	Ξ	
1	9	
,	4	
	2	
	+41 41 675 03 67 —	
	7	
	~	
	Ċ	j
ı	4	)
	`	
	4	t
	_	
٠	7	t
	+	•
	— KN74 Gicywil —	
	-   Word Public   Word Classic   -   Word Classic   -   Word Classic   -   Word Classic   -     Word Classic   -	

Spare parts Water Push Button Order No. 5.18020 / 5.18022		Please note that the safety standards of the equipme must not be affected. Therefore, when carrying out repairs it is helpful to <b>only use original parts</b> .
Order No.	Spare parts	
	Self-righting pressure valve (valid until June 2022) please request repair instructions for replacement	
	Self-righting pressure valve (valid from July 2022) please request repair instructions for replacement	
	Replacement cartridge for self-righting please request repair instructions for replacement	
	Connecting hose with hose protection	
	Pressure reducer	
0.97837	Seal for hose connection	
0.97840	Winter lid	