Instructions for wear The equipment must be checked for Proof of correct operation and safety, especially maintenance checks of play equipment the points listed below: **Operation** Playground..... 1. Carry out an operational test to ensure the Date of installation pump mechanism moves smoothly. Checks depend on the type of equipment. Turn handlebar and grip to ensure they move Any equipment with moving parts must smoothly. be checked at least twice a year, static equipment equipment at least once a year. Check the sprayhead inside the handlebar for proper operation and clean if necessary. Intervals for maintenance work and checks generally depend on 4. Ensure that cranks and pedals are securely connected and check for proper operation. - location - usage 5. Check saddle for wear and tear and ensure it - frequency of use is securely connected. - possible vandalism For more details see also "General Water supply instructions for maintenance of playgrounds". Check hoses for wear and tear, replace if necessary after removing the service lid (located on the side) and the crank. **Pedal Pump** stainless steel with sprayhead inside the 7. Check water supply for wear and tear, and info@ludocrea.ch handlebar clean the suction filter if necessary. Order No. 5.18130 Structural stability 8. Check anchoring to the ground once a year, retighten screws and bolts if necessary. Note 675 03 Prior to the start of the frost period, turn off Special notes, e.g. for repairs water supply and drain the lines, dismantle 1 the pedal pump and drain the water container 4 if necessary. If the pedal pump has been +4] removed, you can close the opening using the included winter lid. Giswil 6074 Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action .udoCrea.ch GmbH All work carried out, everything is in order 6 Maintenance carried out by: Date