

Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground.....

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- usage
- frequency of use
- possible vandalism

For more details see also our general instructions for maintenance of playgrounds!

Spraying head with large flange
Order No. 5.18234 / 5.18810 / 5.18815 / 5.18816 / 5.18817 / 5.18818



Spraying head with small flange
Order No. 5.18236 / 5.18830 / 5.18835 / 5.18836 / 5.18837 / 5.18838



Spraying head

1. Remove the brass spraying head (using a 10 mm Allen wrench) and clean it. Check the rubber seal for damage and replace it if necessary. Screw the spraying head back in (recommendation: apply valve grease or similar to the threads).

Spraying Head with cleaning mechanism (Part No. 5.18810/5.18830):

2. Press down brass knob in order to remove accumulated dirt. If required, remove the semi-spherical cover of the spraying head for better access. When reattaching the cover, make sure the holes of the cover align with those of the nozzle.

Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action

All work carried out, everything is in order

Maintenance carried out by:

..... Date