Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground.....

Date of installation .....

Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- usage
- frequency of use
- possible vandalism

For more details see also our general instructions for maintenance of playgrounds!

Spray Head
with large flange
Order No. 5.18234 / 5.18810 / 5.18815 / 5.18816 / 5.18817 / 5.18818



Spray Head
with small flange
Order No. 5.18236 / 5.18830 / 5.18835 / 5.18836 / 5.18837 / 5.18838

Spray Head

1. Remove the brass Spray Head (using a 10 mm Allen wrench) and clean it. Check the rubber seal for damage and replace it if necessary. Screw the Spray Head back in (recommendation: apply valve grease or similar to the threads). ☐

   Spray Head with cleaning mechanism (Part No. 5.18810/5.18830):

2. Press down brass knob in order to remove accumulated dirt. If required, remove the semi-spherical cover of the Spray Head for better access. When reattaching the cover, make sure the holes of the cover align with those of the nozzle. ☐

Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment	☐	
Repair not carried out, equipment is taken out of action	☐	
All work carried out, everything is in order	☐	

Maintenance carried out by:

..... Date .....

COPYRIGHT © RICHTER SPIELGERÄTE GMBH

En-EN 26.05.2026

LudoCrea.ch GmbH — 6074 Giswil — +41 41 675 03 67 — info@ludocrea.ch