
Instructions for wear checks of play equipment	(	The equipment must be checked for correct operation and safety, especially the points listed below:  Proof of maintenance		
Playground  Date of installation  Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	1.	Carrying cable/cable cappaction		
Intervals for maintenance work and checks generally depend on  - the location - the usage - the frequency of use - possible vandalism  For more details see also "General instructions for maintenance of playgrounds".	3. 4. 5.	Check cable for damage & replace if necessary.  Check articulated cable connection (mountain station) for wear.  Check the slack when no load is placed on the cable by measuring the distance between the line of view and the cable with the assistance of a second person performing the measurement at the check point (= 1.50 m). Re-tension cable according to the sketch.		
Grand Arch Cableway up to 50 m Order No. 6.02110  mountain station  7 at least 40 cm	6. 7.	Pendulum seat  Replace if metal parts are exposed.  Check that ground clearance under the seat = 40 cm min. with no load placed on the seat (1st check 1 week after assembly, 2nd check 4 weeks after assembly, after this regular maintenance intervals), adjust ground if necessary.  Structural stability  Uncover the foundation once a year in order to check for corrosion.		
Re-tensioning Engage the tube (Ø 20 mm, approx. 50 cm long) and remove safety bolts. Tension with no load placed on cable until slack = 1.50 m. Refasten the safety bolts. The cable must be wound around at least 2 times.	R	valley station  Repair not carried out,		Special notes, e.g. for repairs
tube Ø 20 mm	R e A	Repair not carried out, quipment is taken out of action  All work carried out, verything is in order		-
	N	laintenance carried out by: Date		

Spare Parts Grand Arch Cableway Order No. 6.02110



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

Order No.	6.02110	parts.	
Order No.	Spare part	Order No.	Spare part
0.95000	pendulum seat with suspension chain length 1.50 m	0.95051 0.95052	stopper spring for mountain station stopper spring for valley station
		0.95015	rubber buffer for travelling crab with sound muffler
		0.95012	travelling crab
0.94110	pendulum seat without disc		
0.94120	disc for pendulum seat		
0.95080	carrying cable 54 m with 2 hose sleeve segments		