Play value

We developed a new version with a cross beam made of steel to give the Toddler's Twin Swing a special design. The sophisticated corner connection ensures extra stability for the entire construction. No playground is complete without a swing. It is important that children are offered the right equipment to promote development. Swinging to-and-fro is a basic movement and is not just fun for children. Swinging releases stress, has a comforting effect and is very enjoyable, especially done together next to one another.





Order No. 6.12020 Toddler's Swing – special



Order No. 6.12720 Toddler's Twin Swing – special

Fundamental characteristics

- Aesthetically appealing design
- Incentive for playing: repeating
- familiar activities
- Movement: swinging, jumping off

Recommended for

- Children under 3 years
- Kindergarten children
- Supervised play areas, such as kindergartens, schools, after-school
- programmes or similar - Public play areas without supervision,
- such as playgrounds, parks or similar

Toddler's Swing – special Toddler's Twin Swing – special







Order No. 6.12720

6

680

Order No. 6.12020 Toddler's Swing – special





Safety distance	\longrightarrow
Device dimensions	•
Functional distance	—

Safety check according to DIN EN 1176


Components


Order No. 6.12020

- Toddler's Swing special
- Swing with steel feet 1 and cross beam made of steel
- Toddler belt seat with chains

Order No. 6.12720

- Toddler's Twin Swing special Swing with steel feet and cross beam 1 made of steel
- 2 Toddler belt seats with chains





Installation information

corresponding to a fall height of \leq 1.00 m

(please refer to price list for more

Exact measurements may vary; for all installation dimensions refer to current installation instructions.

Technical changes reserved.

Surfacing requirements

detailed information)

Order No. 6.12020

Order No. 6.12720

2 items 60 x 60 x 60 cm

Excavation depth 80 cm

4 items 60 x 70 x 40 cm Excavation depth 60 cm

Foundations

Attention:

Technical information

Equipment made of non-impregnated mountain larch

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced

Swing joint

Drop-forged, hot-dip galvanised swing joint with sintered bush and integrated swivel

Profiled washer

Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt

Sintered bush

For all reciprocating movements we use sintered plain bearings which are self-lubricating in use and can easily be exchanged if necessary

Ground anchor


All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel

Cross beam made of steel

Swing cross beam made of hot-dip galvanized steel.

Optimized swing geometry with rigid corner connections, thus allowing for smaller foundations and easier foundation covering

Chains



Flexible swing seat made of steel reinforced rubber

Order No. 6.12720

As above, but in addition with

Interlocking

Scale 1:100

Interlocking connection, with milled metal rings or serrated disc dowels, to reinforce the bolt connection under high loads transverse to the grain direction of the wood

For more detailed explanation of the quality characteristics see price list.

Dimensions

(small deviations possible)

Order No. 6.12020	
Toddler's Swing – special	
Height	

Height	1.95 m
Vertical clearance	1.70 m
Width	2.25 m
Weight	130 kg

Order No. 6.12720

Toddler's Twin Swing – special		
1.90 m		
1.70 m		
3.70 m		
180 kg		



info@ludocrea.ch I +41 41 675 03 67 6074 Giswil -udoCrea.ch GmbH



6.12020



6.12720