info@ludocrea.ch

Play value

This swing is higher than the Multisurface Swing and also available with metal cross beam. A playground is not complete without a swing. Children need the possibility of swinging during their development. Swinging to and fro is a basic movement and is fun not only for children. Swinging has a comforting effect, removes tensions and provides pleasure, particularly if swinging is possible side by side.









Order No. 6.14020 High Twin Swing special, Photo © Daniel Perales

Fundamental characteristics

- High-quality design
- Special equipment height
- Incentive for playing: swing suspension
- Movement: swinging, jumping off

Recommended for

- School children
- Young people
- Swimming pools without supervision, such as outdoor pools, adventure pools or similar
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar

High Swing special High Twin Swing special








6.13020





Safety check according to DIN EN 1176

Components

Order No. 6.13020 **High Swing special**

- Swing frame with steel feet and crossbeam made of steel
- 1 Rubber seat with Chains

Order No. 6.14020 **High Twin Swing special**

- crossbeam made of steel
- 2 Rubber seats with Chains

Swing frame with steel feet and



6.13020



Installation information

Surfacing requirements corresponding to a fall height of ≤ 2.00 m (please refer to price list for more detailed information)

Foundations

Order No. 6.13020 High Swing special

4 Items 60 x 70 x 40 cm Excavation depth 60 cm

Order No. 6.14020 **High Twin Swing special**

4 Items 60 x 70 x 40 cm Excavation depth 60 cm

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions.

Technical changes reserved.

Technical information

Equipment made of non-impregnated mountain larch

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



Swing seat

Ergonomically shaped swing seat made of rubber with soft shock absorbing edge. Durable due to strong profiled steel insert



Swing joint

Drop-forged, hot-dip galvanised swing joint with sintered bush and integrated swivel



Profiled washer

Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt



Interlocking

Interlocking connection, with milled metal rings or serrated disc dowels, to reinforce the bolt connection under high loads transverse to the grain direction of the wood



Sintered bush

For all reciprocating movements we use sintered plain bearings which are self-lubricating in use and can easily be exchanged if necessary



Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



Cross beam made of steel

Swing cross beam made of hot-dip galvanized steel.



Optimized swing geometry with rigid corner connections, thus allowing for smaller foundations and easier foundation covering

Chains

Chains made of hot-dip galvanized steel (1.4301 / 1.4571 at extra charge) welded before galvanising, short-linked, without eyelets on the connecting parts, easy to exchange and shorten



For more detailed explanation of the quality characteristics see price list.

Dimensions

(small deviations possible)

Order No. 6.13020 **High Swing special**

Height	3.00 m
Vertical clearance	2.80 m
Length	2.95 m
Width	2.25 m
Weight	240 kg

Order No. 6.14020

High Iwin Swing special	
Height	3.00 m
Vertical clearance	2.80 m
Length	4.30 m
Width	2.25 m
Weight	270 kg

