| Instructions for wear checks of play equipment | The equipment must be checked for correct operation and safety, especially the points listed below: | Proof of maintenance |
|--|---|---------------------------------|
| Playground | Wooden parts Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre. Belt Ensure that the slackline is securely connected by checking the belt slings; retighten if necessary. Check belt strap for wear and tear; it must be replaced if there are any cut marks, fraying or similar damage. Additional information Do not use any chemicals, soap or | |
| Slackline Order No. 7.15501 Posts for Slackline Order No. 7.15510 / 7.15610 | detergent for cleaning. When storing the slackline textiles, store in dry and well ventilated rooms. Protect from heat, chemicals, soiling and mechanical damage. Please pay attention to the depicted care symbols. **More points on next page** | Special notes, e.g. for repairs |
| | Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action | |
| | All work carried out, everything is in order | |
| | Maintenance carried out by:Date | |

| Instructions for wear checks of play equipment | The equipment must be checked for correct operation and safety, especially the points listed below: | Proof maint | of enance |
|--|---|----------------|---------------------------------|
| Playground | Ratchet | | |
| Date of installation | 5. Check tensioning lever, sprockets, shack- les and release for cracks and deformation | | |
| Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year. Intervals for maintenance work and checks | (see detailed diagram).6. Check that the interlock mechanism and slotted shaft run smoothly and, if required, lubricate the contact points (see detailed diagram). | | |
| generally depend on - location - usage - frequency of use - possible vandalism | Additional information Belt straps, hoses and iron parts must not be used any longer if one of the following instances occurs: | | |
| For more details see also our general instructions for maintenance of playgrounds! | Yarn breaks or cuts into the fabric deeper than 10 % of the cross-section Damage to the load-bearing seams Deformation as the result of the effects of heat, such as friction | | |
| Slackline Order No. 7.15501 | Knots in the line as a connection between lines or shackles or as tree harness Damage caused by the effects of ag- gressive substances | | |
| Posts for Slackline Order No. 7.15510 / 7.15610 | Deformation, hairline fissures, breaks, widening by more than 5%, significant corrosion or other damage to tensioning or connecting elements such as: deformation of the slotted shaft, release bent, tensioning lever broken or cracked, sprockets worn, shackles deformed or broken | | airs |
| | Structural stability | | or rep |
| 7 | 7. Uncover the foundation once a year in order to check for rot or, in the case of posts made of steel, for corrosion. | | Special notes, e.g. for repairs |
| detailed diagram | | | Spe |
| 5 | Repair not carried out, it is still possible to play on equipment | | |
| | Repair not carried out, equipment is taken out of action | | |
| 5 6 0.5 | All work carried out, everything is in order | | |
| | Maintenance carried out by: | | |