This copy may be copied for maintenance of Richter play equipment. Page 1		
Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
 Playground Date of installation Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year. Intervals for maintenance work and checks generally depend on location usage frequency of use possible vandalism 	 Wooden parts Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. Check that all bolts and screws are tight and retighten if necessary. Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm. Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre. Check steering wheel of function and firm 	
For more details see also our general instructions for maintenance of playgrounds! Fishing Boat Order No. 8.02050	 seated, retighten if necessary. Climbing Net 6. Check connection to wood, if necessary retighten screws/bolts. 7. Check plastic sleeves of the rope and net elements for wear and tear; replace any elements whose inner steel strands are damaged. 8. Ensure that rope and net elements are securely connected and check connection 	
	 points for damage. Attention The maintenance intervals must be strictly adhered to! Structural stability 9. In order to check steel feet for corrosion, uncover the foundations once a year. 	Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
	Maintenance carried out by: 	

COPYRIGHT © RICHTER SPIELGERÄTE GMBH