

Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance			
Playground Date of installation Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year. Intervals for maintenance work and checks generally depend on - location - kind of use - frequency of use - possible vandalism For more details see also "General instructions for maintenance of playgrounds". End frame with ladder for Rope Bridge Order No. L3.66520	Wooden parts 1. Check for rot and, if necessary, smooth splinters and round off sharp edges of cracks. ☐ 2. Check that all bolts and screws are tight and retighten if necessary. ☐ 3. Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre. ☐ 4. Check the ash wood rungs of the ladder for wear and tear, the remaining diameter must be at least 30 mm. ☐ Structural stability 5. In order to check for rot at wooden parts or steel feet for corrosion, uncover the foundations once a year. ☐	Special notes, e.g. for repairs			
	Repair not carried out, it is still possible to play on equipment			☐	
	Repair not carried out, equipment is taken out of action			☐	
	All work carried out, everything is in order			☐	
	Maintenance carried out by: Date				