Play value

© Richter Spielgeräte GmbH

Our Building Site 02 is not just a place for kids to role-play to their heart's content – children of all ages can use sand hoists, shovels, sand pipes and sand chutes to recreate various processes from the 'real' world of construction sites. Motor skills are also required here, as the work platform can be climbed onto and off via ladders or an inclined climbing net.





Fundamental characteristics

- Child-oriented dimensions according to ergonomic knowledge
- Space-defining design and natural wooden surface appeal to the senses
- Offers a range of play opportunities
- Large play area underneath the platform
- Incentive for playing: sand hoists, sand wheel, chains, climbing net, swing, slide
- Movement: physical effort, climbing, swinging, sliding

Recommended for

- Kindergarten children
- School children
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar



Order No. L5.02000 **Building Site 02**



Safety check according to DIN EN 1176

Components

- 1 Platform with steel feet
- 3 Ladders
- 3 Sand hoists with 3 shovels and chain
- 2 Sand pipes
- 2 Sand chutes, 2 levels, 1 sand wheel
- 1 Inclined climbing net,
- Order No. 3.69160

Safety distance Device dimensions Functional distance -

Technical information

Equipment made of non-impregnated mountain larch

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced

Bevel cut

Vertical stand posts with bevelled end grain section as constructive wood preservation measure

Core-free

Sawn-timbers core-free, thus decreasing occurrences of cracking and undesired changes in shape

Tongue and groove

Tongue and groove planks made of 4 cm solid wood, highly resilient, no trickling of dust / sand, protection against direct rain

Hardwood rungs

Climbing rungs made of hardwood (ash) Ø 4.2 cm, milled and mortised, secured against twisting, easy to grip and not cold for children to touch

tion of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm,

laid and glued with very good abrasion resistance, strong sheathing even in the

Richter Hercules type rope Richter Hercules type rope, a combina-

Scale 1:150

Installation information

Surfacing requirements corresponding to a fall height of \leq 1.50 m (please refer to price list for more detailed information)

Sand is required for correct functioning.

Foundations **Building Site** 4 items 60 x 60 x 60 cm Excavation depth 80 cm Order No. 3.69160

Inclined Climbing Net 2 items 50 x 50 x 40 cm Excavation depth 80 cm

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions. Technical changes reserved.

Dimensions

(small deviations possible)

Height	2.55 m
Platform height	1.50 m
Platform floor	1.60 x 2.50 m
Length	4.90 m
Width	2.75 m
Weight	700 kg

case of damage by puncturing **Aluminium rope pressing** Aluminium rope pressing, cylindrically pressed, with rounded ends

S-connectors

S-connectors Ø 8.1 mm, made of high-quality stainless steel, rounded

Rope connection fixed

Fixed rope connection without dangerous openings. Screw connection adjustable and countersunk in the wood

Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel

Chains

2.55 m

Chains made of hot-dip galvanized steel (1.4301 / 1.4571 at extra charge) welded before galvanising, short-linked, without eyelets on the connecting parts, easy to exchange and shorten

For more detailed explanation of the quality characteristics see price list.

Sand pipes made of plastic, wall thickness approx. 7 mm

Sand container made of textile-reinforced rubber belt, 8 mm thick

Sand wheel hot-dip galvanised









-udoCrea.ch GmbH

