Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Wooden parts	
Date of installation	Check for rot and, if necessary, smooth out splinters and round off edges of cracks.	
Checks depend on the type of equipment.  Any equipment with moving parts must be checked at least twice a year, static	Check that wood joints are tight, retighten if necessary	
equipment at least once a year.  Intervals for maintenance work and checks generally depend on	3. Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.	
- location	Operation	
<ul><li>kind of use</li><li>frequency of use</li></ul>	Check mechanical parts for proper operation.	
- possible vandalism	5. Check welded joints for cracks	
For more details see also "General instructions for maintenance of playgrounds".	<ol><li>Apply small amount of grease to moving parts (lubricate).</li></ol>	
	7. Enclosed parts are maintenance-free.	
Wheelchair Swing	Screws/bolts	2)
Order No. 6.29110/L6.29110 6.29130/6.29100/L6.29100	Check that bolts and screws are tight and retighten if necessary.	
	Chains	
	Check chains and connections for wear and tear, replace if necessary.	
	Structural stability	77
	In order to check for rot at wooden parts or steel feet for corrosion, uncover the foundation once a year.	e.g. for repairs
		Special notes,
	Repair not carried out,	Speci
	it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
	Maintenance carried out by:	
	Date	