
This copy may be copied for maintenance of Richter play equipment. Instructions for wear The equipment must be checked for **Proof of** correct operation and safety, especially maintenance checks of play equipment the points listed below: Wooden parts Playground 1. Check for rot and, if necessary, smooth out Date of installation splinters and round off sharp edges of cracks. Checks depend on the type of equipment. 2. Recommendation: apply paraffin wax to the Any equipment with moving parts must upper end grain areas once a year, please be checked at least twice a year, static refer to Order No. 0.90100. equipment at least once a year. Intervals for maintenance work and checks generally depend on - location - kind of use - frequency of use - possible vandalism For more details see also "General instructions for maintenance of playgrounds". **Two Horizontal Bars** Order No. L6.96050/R6.96050



Intervals for maintenance work and checks generally depend on - location - kind of use - frequency of use		Horizontal bars			
	3.	3. Check that connections are tight and retighten screws/bolts if necessary.			
		Structural stability			
 possible vandalism For more details see also "General instructions for maintenance of playgrounds". 	4.	In order to check steel feet for corrosion, uncover the foundations once a year.			
Two Horizontal Bars Order No. L6.96050/R6.96050					
				Special notes, e.g. for repairs	
		pair not carried out, s still possible to play on equipment			
	1	pair not carried out, uipment is taken out of action			
		work carried out, erything is in order			
	Ма	aintenance carried out by:	ı	ı	
For spare parts refer to back of page. Maintenance carried out by: Date					
UCHTER SPIELGERÄTE GMBH · D-83112 FRASDORF · PHONE +49-8052/17980 · FAX 4180					

Spare Pai	rts
Two Horizo	ntal Bars
Order No.	L6.96050/
R6.96050	

Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts.**

Order No. Spare part

